2025/07/05 03:42 1/4 meerstetter

Meerstetter Temperature Controller

Refer to the **official documentation** of the Meerstetter for an **in-depth guide** to setting up and operating the system. The manual is very rigorous and covers everything required. This article just covers the main relevant points.

- Official Website Further information
- Datasheet

- Concise data

Manual

- In depth guides

- Setup guide
- Quick guide for the first setup

Overview


Basic Concept

The Meerstetter temperature controller is used to stabilize objects to a given temperature. It measures the temperature of the object using a thermal resistor and adjusts the object temperature accordingly by driving a heating/cooling element connected to the object.

Functionality

- Temperature stabilisation to sub mK range
- Exact control through software environment
- Easy configuration using autotuning funtion
- Custom programmable temperature ramps
- Temperature monitoring and data logging
- Programmable multi purpose pins for different applications

Hardware



X1: General connections

- · power supply
- · multi purpose pins
- serial connection

X2: Connections for temperature measurement and control

- peltier element/heating foil etc.
- temperature measurement

X3: USB for connection to PC

Software

Meerstetter provides a software for their temperature controller. This software is used to set up and monitor the temperature controller. It also provides a option for data logging. The newest version can be downloaded in the software section of the Official Website.

Basic Setup

If you are setting up a Meerstetter temperature controller for the first time, refer to the

official setup guide

. It takes you through all main steps and introduces you to the service software. The Manual

also covers this topic extensively. Refer to chapter 2.

Power supply

The Meerstetter can operate in a voltage range of **5-24V DC** at a maximum current of **4A**. The current setup for the 1560 nm rio laser diode runs at **18V**.


Connect the pins VIN and GND on X1 to a suitable lab power supply to power the meerstetter.

2025/07/05 03:42 3/4 meerstetter

Peltier Element/Heating Foil

The Meerstetter can run with a peltier element as well as a resistive heating element like a heating foil. The peltier element/resistive heater is connected to the pins 0UT+ and 0UT-. To use it correctly, you must configure the meerstetter accordingly using the service software.

Temperature Sensor



* In case of Pt100 or Pt1000, use 4 wires to connect the Object Temperature Sensor

See page 4 of the

Datasheet

Object Temperature

The Meerstetter can do two-wire as well as four-wire measurement. For this the pins OBJ T° IA, OBJ T° IB, OBJ T° UA and OBJ T° UB on X2 are used. UA and UB for two wire, all four for four wire. Compatible temperature sensors are NTC, PT100 and PT1000.

Sink Temperature

The Meerstetter can also monitor the temperature of itself. This is optional. The temperature sensor is connected to SINK T° A and SINK T° B on X2. For this an NTC is used.

Software

The newest version can be downloaded in the software section of the Official Website.

Refer to the documentation given there to get started. If you want to look something up, refer to the

Manual

Further Options

Status LEDs

To add a status LED to the Meerstetter, you can follow this step-by-step guide:

- connect its anode to any of the pins labelled "RES" using a resistor
- · connect its cathode to GND
- connect the Meerstetter to your PC via a mini-USB B cable
- connect a power supply
 - <fc #ff0000>!</fc> ensure the Meerstetter is connected to a load, otherwise it
 might be damaged * open the Meerstetter control software * make sure the Meerstetter
 is connected correctly and it says "ready" or "running" in the bottom left corner * type in
 "expert" at the bottom control panel and click the button labeled "login" * this makes the
 "Expert" tab show up at the top of the window * click on the tab labelled "Expert" * on the
 right side of the panel there are multiple selection fields labelled "RES1" to "RES8" *
 select the option you want to choose from the drop down menu corresponding to the pin
 the LED is connected to * <fc #ff0000>!</fc> Information on what these options exactly
 mean can be found on pages 47 and 48 of the

manual

write the settings to the Meerstetter using the button in the bottom right corner

Pufferkondensatoren

Data Logging

From:

https://iqwiki.iqo.uni-hannover.de/ - IQwiki

Permanent link:

https://iqwiki.iqo.uni-hannover.de/doku.php?id=groups:mg:meerstetter&rev=1521194253

Last update: 2018/03/16 09:57

