

Atomic clocks

General

- Optical atomic clocks
 , N. Poli et al., arXiv:1401.2378v2 (2014)
- Optical atomic clocks
 , A.D. Ludlow et al., Reviews of modern physics **87** (2015)
- Fritz Riehle, Frequency Standards, WILEY-VCH Verlag GmbH & Co. KGaA, 2004
- Optical dipole trap:
[optical_dipole_trap.pdf](#)

Elements

- Best Clock so far (Stand 11/2016)
<http://www.nature.com/nature/journal/v506/n7486/pdf/nature12941.pdf>
 doi:10.1038/nature12941
- Systematic Evaluation for this <http://www.nature.com/articles/ncomms7896.pdf>
- Best Clock Comparison so far (Stand 11/2016) Comparison of Two Independent Sr Optical Clocks with 1×10^{-17} Stability at 10^3 s:
[physrevlett.109.230801.pdf](#)
- **Mercury:**
 - Comparing a mercury optical lattice clock with microwave and optical frequency standards
 , R. Tyumenev et al., arXiv:1603.02026v2 [physics.atom-ph] 13 Nov 2016

Cavities

Summary of the best cavities

- Mercury (Paris) cavity:
 - Ultrastable lasers based on vibration insensitive cavities
 , J. Millo et al., PR A **79**, 053829 (2009)
 - Laser locking to the Hg199 π^0 – π^0 clock transition with $5.4 \times 10^{-15}/\sqrt{\nu}$ fractional

frequency instability

, J. J. McFerran et al., Optics Letters Vol. **37**, No. 17, 3477-3479 (2012)

General

- Making optical atomic clocks more stable with 10–16-level laser stabilization
, V. Jiang et al., Nature Photonics **5**, 158–161 (2011)
- High-precision laser stabilization via optical cavities
M. Martin and J. Ye

Relevant effects influencing frequency stability

- **Pund-Drever-Hall (PDH):**
 - Laser Phase and Frequency Stabilization Using an Optical Resonator
, R. W. P. Drever et al., Appl. Phys. B **31**, 97-105 (1983)
- **Vibration:**
 - Simple vibration-insensitive cavity for laser stabilization at the 10^{-16} level
, J. Keller et al., Appl. Phys. B **116**, 203–210 (2014)
 - <https://journals.aps.org/pr/abstract/10.1103/PhysRevA.79.053829>
- **Thermal-Noise:**
 - Thermal-Noise Limit in the Frequency Stabilization of Lasers with Rigid Cavities
, K. Numata et al., PRL **93**, 250602 (2004)
 - Thermal noise in optical cavities revisited
, T. Kessler et al., J. Opt. Soc. Am. B Vol. **29**, No. 1 (2012)
- **Residual amplitude modulation:**
 - Reduction of residual amplitude modulation to 1×10^{-6} for frequency modulation and laser stabilization
, W. Zhang et al., Optics Letters Vol. **39**, No. 7 (2014)
 - Investigation and cancellation of residual amplitude modulation in fiber electro-optic modulator based frequency modulation gas sensing technique
, Z. Li et al., Sensors and Actuators B **196**, 23–30 (2014)
 - Residual amplitude modulation in interferometric gravitational wave detector
, K. Kokeyama et al., J. Opt. Soc. Am. A Vol. **31**, No. 1 (2014)
 - Residual Amplitude Modulation in Interferometric Gravitational Wave Detectors
, K. Kokeyama et al., aXiv:1309.4522v1 [gr-qc] 18 Sep 2013
- **ULE compensations rings:**
 - Tuning the thermal expansion properties of optical reference cavities with fused silica mirrors
, T. Legero et al., J. Opt. Soc. Am. B Vol. **27**, No. 5 (2010)

Length

- **7 cm:**

- Compact, thermal-noise-limited optical cavity for diode laser stabilization at 1×10^{-15} , A. D. Ludlow et al., Optics Letters Vol. **32**, Issue 6, pp. 641-643 (2007)

- **10 cm:**

- A compact, robust, and transportable ultra-stable laser with a fractional frequency instability of 1×10^{-15} , Q. F. Chen et al., REVIEW OF SCIENTIFIC INSTRUMENTS 85, 113107 (2014)

- **48 cm:**

- 8×10^{-17} fractional laser frequency instability with a long room-temperature cavity, S. Häfner et al., Optical Letters Vol. **40**, No. 9 (2015)

Mirror layers

- **Crystalline coatings:**

- Tenfold reduction of Brownian noise in high-reflectivity optical coatings, Garrett D. Cole et al., Nature Photonics **7**, 644-650 (2013)

Other geometries

- **Cubic geometry:**

- Force-insensitive optical cavity, S. Webster et al., Optics Letters Vol. **36**, Issue 18, pp. 3572-3574 (2011)
 - PTB took the NPL-design and updated it for a better longterm stability (see Häfner PHD-thesis, Chapter 4.2)

- **Cryogenic single-crystal optical cavities:**

- Ultrastable laser with average fractional frequency drift rate below $5 \times 10^{-19}/s$, C. Hagemann et al., Optics Letters Vol. **39**, No. 17 (2014)
- A sub-40-mHz-linewidth laser based on a silicon single-crystal optical cavity, T. Kessler et al., Nature Photonics Vol. **6**, 687-692 (2012)

Applications

- **Transfer of stability:**

- Providing 10–16 Short-Term Stability of a 1.5- μ m Laser to Optical Clocks, C. Hagemann et. al., IEEE Transactions on instrumentation and measurement, VOL. 62, NO. 6 (2013)

Application of Clocks

- Realization of a timescale with an accurate optical lattice clock:

optica-3-6-563.pdf

- Search for New Physics with Atoms and Molecules: <https://arxiv.org/pdf/1710.01833.pdf>

From:

<https://iqwiki.iqo.uni-hannover.de/> - IQwiki

Permanent link:

<https://iqwiki.iqo.uni-hannover.de/doku.php?id=groups:mg:otherclocks&rev=1507278355>

Last update: **2017/10/06 08:25**

