


Fiberlaser




First start FiberLaser for better autotuning and afterwards Fiber Comb Control for controlling Repetition Rate Stepper Motor and CEO Tuner

Close the program "*Fiber Comb Control*" and lock out the CEO- & REP-PID in the rack, otherwise you can't optimize the comb!

- Push Yes



- Push OK



- If you **turn off and on** the frequency comb, then push in the order:
 1. *Reset*
 2. *Auto on*
 3. *Enable on*



The program is done, if all four boxes [*Laser on, Modelocked, Autoscrumble, Enabled*] are green!


- For **closing** the software:
 1. *Halt*
 2. *Freeze*
 3. Now you can optimize CEO-frequency, therefore play with the arrows *Stg 1-Stg 4* for the

squeezer. Thereby you have to show the CEO-frequency on the Specki and afterwards show the Beat-Signal with 914nm-laser. If one beat is bad, you found a bad modelock point! And don't forget to optimize the Beat-Signal with 914nm-laser with the PCF and SHG controllers!

4. Close the window

- Possible **problems**:

1. If you can't modelocked the laser. Don't worry maybe the fs Laser and Amplifier is off. Then push:
 1. Push *Laser on*
 2. Push *Amplifier on*
2. If the "Scramble Settings arrows" don't move and the step width are 0. Than change the "step width" from 0 to 3 or 5. Afterwards push the " Send" button.



From: <https://iqwiki.iqo.uni-hannover.de/> - IQwiki

Permanent link: <https://iqwiki.iqo.uni-hannover.de/doku.php?id=groups:mg,private:resonatoren:reslabcomputers:fiberlaser&rev=1578995437>

Last update: 2020/01/14 09:50

