

Fiber-Components

- How to work with fiber modulators:

- english:

Modulatorfibel_english

- german:

Modulatorfibel_german

Fiber EOM

Company: [Jenoptik](#)



Do not apply voltages higher than 40V peak-peak to RF input.

- Typ: PM1550

- Center wavelength: 1550 nm
- Insertion loss: 3.0 dB
- Electronic connector: SMA, Inputimpedanz: 50 Ohm
- $U_{pi}@1kHz$: 8.5 V
- Fiber-typ: PM
- Fiber-connector: FC/APC
- Fiber length: 1m
- Crystall: Lithiumniobat (
 Info_crystall
)
- Max optical input power: 300mW cw

- Datasheet:


- german:

Datasheet Fiber-Eom_german

- english:

Datasheet Fiber-Eom_english

- supplied:



Fiber Coupler

50/50


Company: [Opneti](#)

- Typ: CS-PS-A-2x2-1550-50/50-900-5-0.25-FA-3x54
 - Type: PS=PM Fused Coupler
 - Grade: A=Grade
 - Port Type: 2x2
 - Wavelength: 1550
 - Coupling Ratio: 50/50
 - Pigtail Type: 900=900um Loose Tube
 - Fiber Type: 5=Panda Fiber
 - Length: 0.25m
 - Connector: FA=FC/APC
 - Package: $\phi 3.0 \times 54$

- Datasheet:

Datasheet Fiber-coupler_50/50_Opneti

- Test report:



From:
<https://iqwiki.iqo.uni-hannover.de/> - IQwiki

Permanent link:
https://iqwiki.iqo.uni-hannover.de/doku.php?id=groups:mg:project_ptb-cavity:fiber-components&rev=1495011528

Last update: 2017/05/17 08:58

