



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

Mini UHV gate valve, Series 010, DN 40 (ID 1½")
Ordering No. 01032-CE01

Description

Flange	CF-F 40
Actuator	manual
Feedthrough	Bellows

Technical data

Leak rate	– Valve body	$< 5 \cdot 10^{-10} \text{ mbar ls}^{-1}$
	– Valve seat	$< 1 \cdot 10^{-9} \text{ mbar ls}^{-1}$
Pressure range		$1 \cdot 10^{-10} \text{ mbar to 2 bar (abs)}$
Differential pressure on the gate		$\leq 2 \text{ bar}$
Differential pressure at opening		$\leq 30 \text{ mbar}$
Conductance (molecular flow)		220 ls^{-1}
Cycles until first service		50 000
Temperature	– Valve Body	$\leq 250 \text{ °C open} / \leq 200 \text{ °C closed (bake-out max. 24h)}$
(Maximum values: depending on operating conditions and sealing materials)	– Actuator	$\leq 250 \text{ °C}$
Heating and cooling rate		50 °C h^{-1}
Material	– Valve Body	AISI 304 (1.4301), AISI 316L (1.4435)
	– Gate	AISI 304 (1.4301),
	– Bellows	AISI 316L (1.4404, 1.4435)
Seal	– Bonnet	metal
	– Gate	FKM (Viton®), vulcanized
Mounting position		any
Weight		1.5 kg / 3.3 lbs

Created by: MAEM	Release date: 2012-12-06	1 of 1
Modified by:	Release date:	274118EB