



VAT Vakuumventile AG
CH-9469 Haag, Schweiz

Product data sheet

«Easy close» all-metal angle valve, Series 54 DN 40 (ID 1 1/2")

OSL-Article No. 54132-GE02-0001

Description

Flange	DN 40 CF-R
Actuator	manual, hexagon head SW 17 mm or inside $\square \frac{3}{8}"$
Feedthrough	bellows

Technical data

Leak rate	
- To the outside	$< 1 \cdot 10^{-10} \text{ mbar ls}^{-1}$
- Seat	$< 1 \cdot 10^{-10} \text{ mbar ls}^{-1}$
Molecular flow conductance	50 ls ⁻¹
Pressure range	XHV to 2 bar (abs)
Test pressure	1 bar
Differential pressure on the gate	
- in closing and opening direction	$\leq 2 \text{ bar}$
Max. differential pressure at opening	
- in closing and opening direction	1 bar (> 1 bar with reduced cycle life)
Lifetime	$\geq 1'000 \text{ cycles}$
Bake-out temperature (incl. actuator)	$\leq 300^\circ\text{C}$ (open and closed)
Heating and cooling rate	$\leq 60^\circ\text{C h}^{-1}$
Material	
- Body, Mechanism (in contact with media)	1.4404 / 1.4435, AISI 316L
- Bellow	1.4404, AISI 316 L
Seal	
- Bonnet	metal
- Plate	metal
Mounting position	any
Radiation resistance	
- Valve / actuator	10^8 Gy (10^{10} rad)
Turns per stroke	11
Weight	1.9 kg / 4.2 lbs

Attachments

Dimensional drawing No. 505482

Comments

The VAT «Easy close» all-metal angle valves Series 54 are sealed with patented sealing system (hard to hard). During the specified lifetime no service is necessary under clean operating conditions. VAT Series 54 all-metal angle valves use a hexagon head for closing. The valve has not to be closed with a specific closing torque, it is closed to a mechanical stop. No torque wrench is needed to operate the valve.

Created by: Bruno Lenherr	Release date: 01.09.2011	Page 1 of 1
Modified by::	Release date:	291281EA